## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trade mark:	ChiliTec GmbH			
Supplier's addre	ess: -				
Model identifie	r: 21851				
Type of light so	urce:				
Lighting technology used:		LED	Non-directional or directional:	NDLS	
Light source cap-type		Wire			
(or other electric interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein	
Colour-tuneable	e light source:	Nein	Envelope:	-	
High luminance	light source:	Nein			
Anti-glare shield	d:	Nein	Dimmable:	No	
Product parameters					
Parameter		Value	Parameter	Value	
		General product p	arameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		42	Energy efficiency class	G	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 400 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 900	
On-mode power (P <sub>on</sub> ), expressed in W		42,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	-	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set		
Outer	Height	-	Spectral power	See image	
dimensions without	Width	-	distribution in the	in last page	
	Depth	-			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	- -			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	-			
the lumen maintenance factor	-					

(a)'-': not applicable; (b)'-': not applicable;