Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ChiliTec GmbH

Supplier's address: -

Model identifier: 22366

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	Plug				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	No		
Product parameters					

General product parameters:Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer50Energy efficiency classGUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)3 100 in Wide cone (120°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set3 000On-mode power (Pon), expressed in W rounded to the second decimal50,0Standby power (Psb), expressed in W and rounded to the second decimal-Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set-Outer dimensionsHeight-Spectral ower distribution in the distribution in the			i iouuce puidi		1		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer50Energy efficiency classGUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)3 100 in Wide cone (120°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set3 000On-mode power (Pon), expressed in W50,0Standby power (Psb), expressed in W and rounded to the second decimal-Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set-Outer dimensionsHeight Width-Spectral power distribution in theSee image in last page	Parameter		Value	Parameter	Value		
mode (kWh/1000 h), rounded up to the nearest integerclassclassUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)3 100 in Wide cone (120°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set3 000On-mode power (Pon), expressed in W50,0Standby power (Psb), expressed in W and rounded to the second decimal-Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set-Outer dimensionsHeight Width-Spectral power distribution in theSee image in last page	General product parameters:						
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)cone (120°)temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be setOn-mode expressed in W50,0Standby power (P_{sb}), expressed in W and rounded to the second decimal-Networked standby power (P_net) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be setOuter dimensionsHeight-Spectral power distribution in theSee image in last page	mode (kWh/10	00 h), rounded	50		G		
expressed in W expressed in W and rounded to the second decimal Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal for CLS, expressed in W and rounded to the second decimal Outer Height - Guident - Width - Width - Height - Height - Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set Spectral power See image in last page	indicating if it r in a sphere (3 cone (120º) or i	efers to the flux 60°), in a wide		temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that	3 000		
for CLS, expressed in W and rounded to the second decimal index, rounded to to the nearest integer, or the nearest integer, or the range of CRI-values that can be set Outer Height - Spectral power See image in last page Width - distribution in the in last page	•	oower (P _{on}),	50,0	expressed in W and rounded to the	-		
dimensions Width _ distribution in the in last page	for CLS, expres	ssed in W and	-	index, rounded to the nearest integer, or the range of CRI- values that can be			
		Height	-	Spectral power	See image		
without		Width	-	distribution in the	in last page		
		Depth	-	1	Seite 1 / 2		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	-			
the lumen maintenance factor	-					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;