## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: ChiliTec GmbH   |                            |                            |  |              |  |   |
|--|----------------------------|----------------------------|--|--------------|--|---|
|  |                            |                            |  |              |  | Supplier's address: Technik, Bäckerberg 12, 38165 Lehre, DE |
| Model identifie  | r: 22980                   |                            |  |              |  |   |
| Type of light so   | urce:                      |                            |  |              |  |   |
| Lighting techno  | logy used:                 | LED                        | Non-directional or directional:  | NDLS         |  |   |
| Light source cap   | Light source cap-type Wire |                            |  |              |  |   |
| (or other electric interface)  |                            |                            |  |              |  |   |
| Mains or non-m   | nains:                     | MLS                        | Connected light source (CLS):  | Nein         |  |   |
| Colour-tuneable  |                            | Nein                       | Envelope:  | -            |  |   |
| High luminance   | light source:              | Nein                       |  |              |  |   |
| Anti-glare shield:   |                            | Nein                       | Dimmable:  | No           |  |   |
| Product parameters   |                            |                            |  |              |  |   |
| Parameter  |                            | Value                      | Parameter  | Value        |  |   |
| General product parameters:  |                            |                            |  |              |  |   |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                            | 5                          | Energy efficiency class  | G            |  |   |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                            | 300 in Wide<br>cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000        |  |   |
| On-mode power (P <sub>on</sub> ), expressed in W   |                            | 5,0                        | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |  |   |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                            | -                          | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80           |  |   |
| Outer  | Height                     | -                          | Spectral power   | See image    |  |   |
| dimensions<br>without  | Width                      | -                          | distribution in the  | in last page |  |   |
| WICHOUL  | Depth                      | -                          |  |              |  |   |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)   |      | range 250 nm to 800<br>nm, at full-load                |          |  |  |  |
|--|------|--|----------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | -    | If yes, equivalent power (W)                           | -        |  |  |  |
|  |      | Chromaticity coordinates (x and y)                     |          |  |  |  |
| Parameters for LED and OLED light sources:   |      |  |          |  |  |  |
| R9 colour rendering index value  | -    | Survival factor  | -        |  |  |  |
| the lumen maintenance factor   | -    |  |          |  |  |  |
| Parameters for LED and OLED mains light sources:   |      |  |          |  |  |  |
| displacement factor (cos φ1)   | -    | Colour consistency in McAdam ellipses                  | -        |  |  |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.  Flicker metric (Pst LM) | _(b) | If yes then replacement claim (W)  Stroboscopic effect | <u>-</u> |  |  |  |
|  |      | metric (SVM)   |          |  |  |  |

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;