## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: ChiliTec GmbH

Supplier's address: -

## Model identifier: 23021

## Type of light source:

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS |  |  |  |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type         | Plug |                                 |      |  |  |  |
| (or other electric interface) |      |                                 |      |  |  |  |
| Mains or non-mains:           | MLS  | Connected light source (CLS):   | Nein |  |  |  |
| Colour-tuneable light source: | Nein | Envelope:                       | -    |  |  |  |
| High luminance light source:  | Nein |                                 |      |  |  |  |
| Anti-glare shield:            | Nein | Dimmable:                       | No   |  |  |  |
| Product parameters            |      |                                 |      |  |  |  |

|  |                                   | i iodace para                |   | T            |  |  |
|--|-----------------------------------|------------------------------|---|--------------|--|--|
| Parameter  |                                   | Value                        | Parameter   | Value        |  |  |
| General product parameters:  |                                   |                              |   |              |  |  |
| Energy consun<br>mode (kWh/10<br>up to the neares                                      | 00 h), rounded                    | 100                          | Energy efficiency<br>class  | F            |  |  |
| Useful luminou<br>indicating if it re<br>in a sphere (36<br>cone (120º) or in<br>(90º) | efers to the flux 50°), in a wide | 8 350 in Wide<br>cone (120°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 4 000        |  |  |
| On-mode p<br>expressed in W  | ower (P <sub>on</sub> ),          | 100,0                        | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | -            |  |  |
| Networked stand<br>for CLS, express<br>rounded to the s                                | sed in W and                      | -                            | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  |              |  |  |
| Outer  | Height                            | -                            | Spectral power  | See image    |  |  |
| dimensions   | Width                             | -                            | distribution in the   | in last page |  |  |
| without  | Depth                             | -                            | 1   | Soite 4/2    |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre)       |      | range 250 nm to 800<br>nm, at full-load  |   |  |  |  |
|--|------|--|---|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | -    | If yes, equivalent power (W)             | - |  |  |  |
|  |      | Chromaticity<br>coordinates (x and y)    |   |  |  |  |
| Parameters for LED and OLED light sources:   |      |  |   |  |  |  |
| R9 colour rendering index value  | -    | Survival factor                          | - |  |  |  |
| the lumen maintenance factor   | -    |  |   |  |  |  |
| Parameters for LED and OLED mains light sources:   |      |  |   |  |  |  |
| displacement factor (cos φ1)   | -    | Colour consistency<br>in McAdam ellipses | - |  |  |  |
| Claims that an LED light<br>source replaces a fluorescent<br>light source without integrated<br>ballast of a particular wattage. | _(b) | If yes then<br>replacement claim<br>(W)  | - |  |  |  |
| Flicker metric (Pst LM)  | -    | Stroboscopic effect<br>metric (SVM)      | - |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;